



148' Spools 65' Spools and Custom Cuts

SKU#: RLL120H-45*

CC-H-* (Custom Cut, Specify Length - 19.5" intervals)
(Multi-Colored - 21.5" intervals)

B-Blue, CW-Cool White, F-Fuchsia, G-Green, M-Multi, O-Orange, P-Purple, R-Red, RWB-Red/White/Blue, RWB2-Red/White/Blue, T-Teal, WW-Warm White, Y-Yellow, BCW-Blue/Cool White, RCW-Red/Cool White, RG-Red/Green

PRODUCT INFORMATION:

Brilliant Brand LED Rope lights consist of bright and durable LEDs encased in high quality PVC tubing and can be used in virtually any lighting application due to their extreme versatility. LED rope lights will save up to 80% in energy costs, last longer, and are almost indestructible compared to incandescent rope lights. There are also many different lighting effects, through use of controllers, which allow you to dim, fade and flash with LED rope light.

BENEFITS:

Durability - LED rope lights are known for their strength and flexibility. LED bulbs will last longer, hold up in cold weather, and are less prone to failure than incandescent rope lights.

Bend It - Brilliant LED rope lights use a premium UV resistant PVC that allows for enhanced flexibility, a tighter bend radius, making them easily adaptable to the most complicated projects.


Efficient Longevity - LEDs drastically produce more light compared to incandescent, but only uses a fraction of the energy. You can realize up to 80% energy saving and expect a 3-times longer running life with LED rope lights.

SPECIFICATIONS

- Input: 120V AC
- Power Consumption: 1.1 Watts/ft
- Colors: Blue-B, Cool White-CW, Fuchsia-F, Green-G, Multi Colored-M, Orange-O, Purple-P, Red-R, Red White Blue-RWB, Red White Blue-RWB2, Warm White-WW, Yellow-Y, Blue+Cool White-BCW, Red+Cool White-RCW, Red+Green-RG
- LED Count: 12 LEDs/ft
- Lumen Output: up to 7.5 lumens/LED
- LED Spacing: 1.0"
- Light Output: Omni-Directional
- Lifetime: 100,000 Hours
- Dimensions: 0.5" Diameter
- Materials: PVC with UV Protectant Additive
- Temperature rating: -20° F - 130° F
- Max run length: Standard power cord: 492'
High Output Rectifier: 600'
- Cutting Interval: 19.5"
- Ingress Protection: IP44 (IP65 with properly sealed connections)
- Dimmable: Yes, with LED compatible dimmer
- Warranty: 2 Years



LISTED



12.7 mm